



Pin No	Address
1	AGC
2	V_T
3	UHF
4	VHF H
5	VHF L
6	V_S
7	n.c.
8	n.c.
9	n.c.
10	IF2/GND
11	IF1

➤ Features

- Members of the KS-H-130 family small sized VHF/Hyperband/UHF tuners
- Systems CCIR: B/G, H; OIRT: D/K
- Voltage synthesized tuning (VST)
- Off-air channels, S-cable channels and Hyperband
- World standardized mechanical dimensions and world standard pinning
- Compact size
- Comply to “CENELEC EN55020” and “EN55013”

➤ Application

- For TV and VCR

➤ Electrical data

Model No		KS-H-135 E	KS-H-135 EA	KS-H-135 O	KS-H-135 OA
Receiving system		CCIR B/G		OIRT D/K	
Channel selection system		VST			
RF input type (standard)		IEC-14 Female			
Input frequency p.c., MHz	VHF-L	48,25-154,25		49,75-151,25	
	VHF-H	161,25-439,25		159,25-439,25	
	UHF	447,25-855,25		447,25-855,25	
Input impedance, Ω		75			
Input VSWR, max		5			
IF output type		Symmetrical	Asymmetrical	Symmetrical	Asymmetrical
Intermediate frequency, MHz	Picture	38,9		38,0	
	Sound	33,4		31,5	
Power supply, V/mA		5/65			
Tuning voltage supply, V		0,5 – 28			
AGC range (4-0,3V), dB, min	VHF-L, VHF-H	45			
	UHF	40			
Voltage gain, dB, min		38			
Noise figure, dB, max	VHF-L, VHF-H	9			
	UHF	9			
	VHF-L	66			
Image rejection, dB, min	VHF-H	60			
	UHF	50			
IF rejection, dB, min		65			