

Характеристики	Серии DIP-переключателей							
	ВДМ1	DS	DP	DM	RH3	RH3H		
Шаг, мм	2,5	2,54						
Сопротивление контактов, Ом	0,1							
Максимальная нагрузка (без переключения)	100мА, 50В	100мА, 50В	100мА, 50В	100мА, 50В	100мА, 50В	100мА, 50В		
Рабочая нагрузка (при переключении)	25мА, 24В	25мА, 24В	25мА, 24В	25мА, 24В	25мА, 24В	25мА, 24В		
Кол-во переключений при рабочей нагрузке (min)	10000	2000			20000			
Усилие при переключении, гс	не более 800	1000	400	1000	400			
Рабочая температура	-40...+70°C							
Материал корпуса	Термопластик, усиленный стекловолокном (стандарт UL-94V-0)							
Материал контактов	Фосфористая бронза	Никель, напыление золотом						

Модель	Количество переключателей	Размер	
	п	А, мм	В, мм
ВДМ1-2	2	4,9	2,9
ВДМ1-4	4	9,9	7,9
ВДМ1-6	6	14,9	12,9
ВДМ1-8	8	19,9	17,9

Technical drawing of the 74VHC00 package showing top, side, and pin details. The top view shows a rectangular package with dimensions 14mm (pin pitch), 1mm (pin width), 6.9mm (max height), 0.54mm (pin offset), 0.6mm (pin width), 3.2mm (pin length), and 0.15mm (pin thickness). The side view shows a maximum height of 6.9mm and a pin length of 3.2mm. The pin details show a pin pitch of 1.6mm, a pin width of 0.15mm, and a pin length of 7.62mm (±0.5mm). The package is labeled with 'ON' and 'DIP' and has pins numbered 1 through 8.

Модель	Кол-во	Размер	
	переключателей	А, мм	В, мм
DS - 2	2	6,44	2,54
DS - 3	3	8,98	5,08
DS - 4	4	11,52	7,62
DS - 5	5	14,06	10,16
DS - 6	6	16,6	12,7
DS - 7	7	19,14	15,14
DS - 8	8	21,68	17,78
DS - 9	9	24,22	20,32
DS - 10	10	26,76	22,86
DS - 12	12	31,84	27,94

Technical drawing of the 10-pin DIP package showing top, side, and bottom views with dimensions in millimeters.

Top View Dimensions:

- Pin pitch: 2.54 mm
- Pin width: 0.6 mm
- Pin spacing (center-to-center): 2.54 mm
- Pin length: 1.3 mm
- Pin height: 10.3 mm (max)
- Pin numbering: 1 to 10, with "DIP" and "ON" labels.

Side View Dimensions:

- Pin height: 10.3 mm (max)
- Pin width: 0.6 mm
- Pin spacing (center-to-center): 2.54 mm
- Pin length: 1.3 mm
- Pin height: 10.3 mm (max)

Bottom View Dimensions:

- Pin pitch: 2.54 mm
- Pin width: 0.6 mm
- Pin spacing (center-to-center): 2.54 mm
- Pin length: 1.3 mm
- Pin height: 10.3 mm (max)
- Pin numbering: 1 to 10, with "DIP" and "ON" labels.

Other Dimensions:

- Pin width: 0.6 mm
- Pin spacing (center-to-center): 2.54 mm
- Pin length: 1.3 mm
- Pin height: 10.3 mm (max)
- Pin numbering: 1 to 10, with "DIP" and "ON" labels.

Модель	Количество переключателей	Размер	
	п	А, мм	В, мм
DP - 2	2	6,44	2,54
DP - 3	3	8,98	5,08
DP - 4	4	11,52	7,62
DP - 5	5	14,06	10,16
DP - 6	6	16,6	12,7
DP - 7	7	19,14	15,14
DP - 8	8	21,68	17,78
DP - 9	9	24,22	20,32
DP - 10	10	26,76	22,86
DP - 12	12	31,84	27,94

Модель	Количество переключателей	Размер	
	n	A, мм	B, мм
DM - 2	2	6,02	2,54
DM - 4	4	11,1	7,62
DM - 6	6	16,18	12,7
DM - 8	8	21,26	17,78
DM - 10	10	26,34	22,86