

- **Surface Acoustic Wave Resonator Filter**
- **Low-Loss, Coupled-Resonator Quartz Design**
- **Simple External Impedance Matching**
- **F-16 Metal Thru-Hole Package**

SF90.5B

Absolute Maximum Rating (Ta=25°C)		
Parameter	Rating	Unit
Input Power Level P_{in}	0	dBm
DC Voltage VDC Between Any Two Pins V_{DC}	30	V
Operating Temperature Range T_A	-10 ~ +60	°C
Storage Temperature Range T_{stg}	-40 ~ +85	°C




Electrical Characteristics					
Parameter	Sym	Minimum	Typical	Maximum	Unit
Center Frequency (25°C)	f_c	NS	90.50	NS	MHz
Insertion Loss at f_c	IL	-	2.0	4.0	dB
3dB Bandwidth	BW_3	45	62	-	KHz
Passband Ripple ($f_c \pm 15$ KHz)	$\Delta\alpha$	-	0.2	1.0	dB
Stopband Attenuation	$f_c \pm 60$ KHz	15	21	-	dB
	$f_c \pm 120$ KHz	42	47	-	dB
	$f_c - 930 \dots f_c - 890$ KHz	55	62	-	dB
	$f_c - 4020 \dots f_c - 3980$ KHz	70	80	-	dB
Temperature Stability	Turnover Temperature	T_0	25	-	°C
	Frequency Temperature Coefficient	FTC	-	0.032	ppm/°C
Group Delay	Absolute at f_c	τ	10	15	μSec
	Deviation $f_c \pm 10$ KHz	$\Delta\tau$	-	2.0	μSec
DC Insulation Resistance Between any Two Pins		-	1.0	-	MΩ

NS = Not Specified

Notes:

- The frequency f_c is defined as the midpoint between the 3dB frequencies.
- Unless noted otherwise, all measurements are made with the filter installed in the specified test fixture that is connected to a 50Ω test system with VSWR $\leq 1.2:1$. The test fixture L and C are adjusted for minimum insertion loss at the filter center frequency, f_c . Note that insertion loss, bandwidth, and passband shape are dependent on the impedance matching component values and quality.
- Unless noted otherwise, specifications apply over the entire specified operating temperature range.
- Frequency aging is the change in f_c with time and is specified at +65°C or less. Aging may exceed the specification for prolonged temperatures above +65°C. Typically, aging is greatest the first year after manufacture, decreasing in subsequent years.
- Turnover temperature, T_0 , is the temperature of maximum (or turnover) frequency, f_0 . The nominal frequency at any case temperature, T_c , may be calculated from: $f = f_0 [1 - FTC (T_0 - T_c)^2]$.
- The specifications of this device are based on the test circuit shown above and subject to change or obsolescence without notice.
- All equipment designs utilizing this product must be approved by the appropriate government agency prior to manufacture or sale.
- Our liability is only assumed for the Surface Acoustic Wave (SAW) component(s) per se, not for applications, processes and circuits implemented within components or assemblies.
- For questions on technology, prices and delivery please contact our sales offices or e-mail sales@vanlong.com.

Package Dimensions (F-16)



Electrical Connections

Terminals	Connection
1	Input / Output
2	Case Ground
3	Case Ground
4	Output / Input

Package Dimensions

Dimensions	Nom (mm)	Dimensions	Nom (mm)
A	12.0	E	5.0
B	7.2	F	2.54
C	2.0	G	0.5
D	3.5		


Marking

SF90.5B

Ink Marking

Color: Black or Blue

Test Circuit



L = 12~20 turns of 0.51mm insulated copper, 4.0mm ID

Typical Frequency Response

