

规格书编号

SPEC NO :

产品规格书

SPECIFICATION

CUSTOMER 客 户 : _____

PRODUCT 产 品 : _____ SAW FILTER _____

MODEL NO 型 号 : _____ HD BF115A SIP5D _____

PREPARED 编 制 : _____ CHECKED 审 核 : _____

APPROVED 批 准 : _____ D A T E 日 期 : _____ 2011-2-22 _____

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子有限公司
Shoulder Electronics Limited

更改历史记录

History Record

[illegible]

1.SCOPE


SHOULDER's SAW filter series have broad line up products meeting all broadcast standard including NTSC,PAL and SECAM systems. These filters are composed of two interdigital transducers on a single-crystal, piezoelectrical chip. they are used in electronic equipments such as TV and so on.

2.Construction


2.1 Dimension and materials

Manufacturer's name : SHOULDER ELECTRONICS Co. LTD(CHINA)

Type : HD BF115A



2.2. Circuit construction, measurement circuit



3.Characteristics

Items	Conditions	Specifications
Standard atmospheric conditions	Unless otherwise specified , the standard rang of atmospheric conditions for making measurements and tests is as follows; Ambient temperature : 15°C to 35°C Relative humidity : 25% to 85% Air pressure : 86kPa to 106kPa	There shall be no damage.
Operating temperature rang	Operating temperature rang is the rang of ambient temperatures in which the filter can be operated continuously. -20°C ~ +60°C	
Storage temperature rang	Storage temperature rang is the rang of ambient temperatures at which the filter can be stored without damage. Conditions are as specified elsewhere in these specifications. -40°C ~ +70°C	
Reference temperature	+25°C	

3.1 Maximum Rating

DC voltage	VDC	12	V	Between any terminals
AC voltage	Vpp	10	V	Between any terminals

3.2 Electrical Characteristics


Source impedance $Z_s=50\Omega$

Load impedance $Z_L=50\Omega$ $T_A=25^\circ\text{C}$

Item	Freq	min	typ	max	
Center frequency	Fo	-	115.24	-	MHz
Insertion attenuation Reference level	115.24MHz	21.0	22.5	24.0	dB
Amplitude(p-p)	114.0~116.5 MHz		0.6		dB
Pass bandwidth	B _{1.5dB}	-	2.9	-	MHz
	B _{15dB}	-	3.9	-	MHz
	B _{30dB}	-	4.4	-	MHz
Relative attenuation	105.0~111.0 MHz	40.0	45.0	-	dB
	111.0~112.5 MHz	35.0	45.0	-	dB
	118.0~119.5 MHz	36	46.0	-	dB
	119.5~125.0 MHz	40	45	-	dB
Reflected wave signal suppression 1.5μs...6.0μs after main pulse (Test pulse 250μs, carrier frequency 115.24MHz)		38.0	48.0	-	dB
Group delay ripple(p-p) 113.79~116.69			70		ns
Impedance at 36.00MHz Input: $Z_{in}=R_{in} // C_{in}$ Output: $Z_{out}=R_{out} // C_{out}$			0.2//16.0 0.1//23.4		KΩ//pF KΩ//pF
Temperature coefficient			-18		ppm/k

3.3 Environmental Performance Characteristics

Item	Condition	Specifications																				
High temperature	The specimen shall be store at a temperature of 80±2°C for 96±4h. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.	Mechanical characteristics and specifications in electrical characteristics shall be satisfied. There shall be no excessive change in appearance.																				
Low temperature	The specimen shall be store at a temperature of -20±3°C for 96±4h. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.																					
Humidity	The specimen shall be store at a temperature of 40±2°C with relative humidity of 90% to 96% for 96±4h. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.																					
Thermal shock	The specimen shall be subjected to 8 continuous cycles each as shown below. Then it shall be subjected to standard atmospheric conditions for 1h, after which measurement shall be made within 1h.																					
	<table><tr><td></td><td>Temperature</td><td>Duration</td></tr><tr><td>1</td><td>+25 °C=>-40 °C</td><td>0.5h</td></tr><tr><td>2</td><td>-40 °C</td><td>4h</td></tr><tr><td>3</td><td>-40 °C=>+85 °C</td><td>2h</td></tr><tr><td>4</td><td>+85 °C</td><td>4h</td></tr><tr><td>5</td><td>+85 °C =>+25 °C</td><td>0.5h</td></tr><tr><td>6</td><td>+25 °C</td><td>1h</td></tr></table>			Temperature	Duration	1	+25 °C=>-40 °C	0.5h	2	-40 °C	4h	3	-40 °C=>+85 °C	2h	4	+85 °C	4h	5	+85 °C =>+25 °C	0.5h	6	+25 °C
		Temperature	Duration																			
	1	+25 °C=>-40 °C	0.5h																			
	2	-40 °C	4h																			
	3	-40 °C=>+85 °C	2h																			
	4	+85 °C	4h																			
	5	+85 °C =>+25 °C	0.5h																			
6	+25 °C	1h																				
Resistance to Soldering heat	Reflow soldering method Peak: 255 ±5 °C, 220 ±5 °C, 40s At electrode temperature of the specimen.																					


	 <p>The specimen shall be passed through the reflow furnace with the condition shown in the above profile for 1 time.</p> <p>The specimen shall be stored at standard atmospheric conditions for 1h, after which the measurement shall be made. Test board shall be 1.6 mm thick. Base material shall be glass fabric base epoxy resin.</p>	
Solder ability	Immerse the pins melt solder at 260°C+5/-0°C for 5 sec.	More then 95% of total area of the pins should be covered with solder

3.4 Mechanical Test

Items	Conditions	Specifications
Vibration	600-3300rpm amplitude 1.5mm 3 directions 2 H each	There shall be no damage.
Drop	On maple plate from 1 m high 3 times	
Lead pull	Pull with 1 kg force for 30 seconds	
Lead bend	90° bending with 500g weigh 2 times	

3.5 Voltage Discharge Test

Item	Condition	Specifications
------	-----------	----------------

Surge	<p>Between any two electrode</p> 	There shall be no damage
-------	--	--------------------------

3.6 Frequency response

