

规格书编号

SPEC NO :

# 产品规格书

# SPECIFICATION

CUSTOMER 客 户 : \_\_\_\_\_

PRODUCT 产 品 : \_\_\_\_\_ SAW FILTER

MODEL NO 型 号 : \_\_\_\_\_ HDF425A F11

PREPARED 编 制 : \_\_\_\_\_ CHECKED 审 核 : \_\_\_\_\_

APPROVED 批 准 : \_\_\_\_\_ D A T E 日 期 : \_\_\_\_\_ 2006-5-11

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子股份有限公司

Shoulder Electronics Limited



## 更改历史记录

## History Record

[illegible]

## 1. SCOPE


This specification shall cover the characteristics of SAW filter With F425A used for the page system.

## 2. ELECTRICAL SPECIFICATION

DC Voltage VDC	10V
AC Voltage Vpp	10V50Hz/60Hz
Operation temperature	-20°C to +60°C
Storage temperature	-45°C to +85°C
RF Power Dissipation	0dBm

### Electronic Characteristics

#### 2-1. Typical frequency response




#### 2-2. Electrical characteristics


Part number	F425A	Unit
Nominal center frequency (Fo)	425	MHz
Insertion Loss		
1.fo-45.8~fo-39.8 MHz	50min.	dB
2.fo±3.0 MHz	4.0max.	
3.fo +39.8~ fo +45.8MHz	45min.	
Ripple (with Fo ±3.0MHz)	2.0max	dB
Input/Output Impedance(Nominal)	50//0	Ω/pF



### 3 . TEST CIRCUIT



### 4. DIMENSION



## **5. ENVIRONMENTAL CHARACTERISTICS**

### **5-1 High temperature exposure**

Subject the device to +85°C for 16 hours. Then release the filter into the room conditions for 24 hours prior to the measurement. It shall fulfill the specifications in table 1.

### **5-2 Low temperature exposure**

Subject the device to -20°C for 16 hours. Then release the device into the room conditions for 24 hours prior to the measurement. It shall fulfill the specifications in table 1.

### **5-3 Temperature cycling**

Subject the device to a low temperature of -40°C for 30 minutes. Following by a high temperature of +80°C for 30 Minutes. Then release the device into the room conditions for 24 hours prior to the measurement. It shall meet the specifications in table 1.

### **5-4 Resistance to solder heat**

Dip the device terminals no closer than 1.5mm into the solder bath at 260°C±10°C for 10 ±1 sec. Then release the device into the room conditions for 4 hours. The device shall meet the specifications in table 1.

### **5-5 Solderability**

Subject the device terminals into the solder bath at 245°C±5°C for 5s, More than 95% area of the terminals must be covered with new solder. It shall meet the specifications in table 1.

### **5-6 Mechanical shock**

Drop the device randomly onto the concrete floor from the height of 1m 3 times. the device shall fulfill the specifications in table 1.

### **5-7 Vibration**

Subject the device to the vibration for 1 hour each in x,y and z axes with the amplitude of 1.5 mm at 10 to 55 Hz. The device shall fulfill the specifications in table 1.

### **5-8 Lead fatigue**

#### **5-8-1 Pulling test**

Weight along with the direction of lead without an shock 1kg. The device shall satisfy all the initial Characteristics.

#### **5-8-2 Bending test**

Lead shall be subject to withstand against 90°C bending with 450g weight in the direction of thickness. This operation shall be done toward both direction. The device shall show no evidence of damage and shall satisfy all the initial electrical characteristics.

## **6. REMARK**

#### 6.1 Static voltage

Static voltage between signal load & ground may cause deterioration & destruction of the component. Please avoid static voltage.

#### 6.2 Ultrasonic cleaning

Ultrasonic vibration may cause deterioration & destruction of the component. Please avoid ultrasonic cleaning

#### 6.3 Soldering

Only leads of component may be soldered. Please avoid soldering another part of component.