

MAC97A8; MAC97A6

Logic level triac

Rev. 01 — 29 March 2001

Product specification

1. Description

Logic level sensitive gate triac intended to be interfaced directly to microcontrollers, logic integrated circuits and other low power gate trigger circuits.

Product availability:

MAC97A8 in SOT54 (TO-92)

MAC97A6 in SOT54 (TO-92) available on request - contact your sales representative.

2. Features

- Blocking voltage to 600 V (MAC97A8)
- RMS on-state current to 0.6 A
- Sensitive gate in all four quadrants
- Low cost package.

3. Applications

- General purpose bidirectional switching
- Phase control applications
- Solid state relays.

4. Pinning information

Table 1: Pinning - SOT54 (TO-92), simplified outline and symbol

Pin	Description	Simplified outline	Symbol
1	main terminal 2		
2	gate		
3	main terminal 1		

SOT54 (TO-92)



PHILIPS

5. Quick reference data

Table 2: Quick reference data

Symbol	Parameter	Conditions	Typ	Max	Unit
V_{DRM}	repetitive peak off-state voltage				
	MAC97A8	$T_j = 25 \text{ to } 125 \text{ }^\circ\text{C}$	–	600	V
	MAC97A6	$T_j = 25 \text{ to } 125 \text{ }^\circ\text{C}$	–	400	V
$I_{\text{T(RMS)}}$	on-state current (RMS value)	full sine wave; $T_{\text{lead}} \leq 50 \text{ }^\circ\text{C}$; Figure 5	–	0.6	A
I_{TSM}	non-repetitive peak on-state current		–	8.0	A

6. Limiting values

Table 3: Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DRM}	repetitive peak off-state voltage				
	MAC97A8	$T_j = 25 \text{ to } 125 \text{ }^\circ\text{C}$	–	600	V
	MAC97A6	$T_j = 25 \text{ to } 125 \text{ }^\circ\text{C}$	–	400	V
$I_{\text{T(RMS)}}$	on-state current (RMS value)	full sine wave; $T_{\text{lead}} \leq 50 \text{ }^\circ\text{C}$; Figure 5	–	0.6	A
I_{TSM}	non-repetitive peak on-state current	full sine wave; $T_j = 25 \text{ }^\circ\text{C}$ prior to surge			
		$t = 20 \text{ ms}$	–	8.0	A
		$t = 16.7 \text{ ms}$	–	8.8	A
I^2t	I^2t for fusing	$t = 10 \text{ ms}$	–	0.32	A^2s
di_T/dt	repetitive rate of rise of on-state current after triggering	$I_{\text{TM}} = 1.0 \text{ A}$; $I_{\text{G}} = 0.2 \text{ A}$; $di_{\text{G}}/dt = 0.2 \text{ A}/\mu\text{s}$			
		T2+ G+	–	50	$\text{A}/\mu\text{s}$
		T2+ G–	–	50	$\text{A}/\mu\text{s}$
		T2– G–	–	50	$\text{A}/\mu\text{s}$
		T2– G+	–	10	$\text{A}/\mu\text{s}$
I_{GM}	gate current (peak value)	$t = 2 \text{ } \mu\text{s}$ max	–	1	A
V_{GM}	gate voltage (peak value)	$t = 2 \text{ } \mu\text{s}$ max		5	V
P_{GM}	gate power (peak value)	$t = 2 \text{ } \mu\text{s}$ max	–	5	W
$P_{\text{G(AV)}}$	average gate power	$T_{\text{case}} = 80 \text{ }^\circ\text{C}$; $t = 2 \text{ } \mu\text{s}$ max	–	0.1	W
T_{stg}	storage temperature		–40	+150	$^\circ\text{C}$
T_j	operating junction temperature		–40	+125	$^\circ\text{C}$

7. Thermal characteristics

Table 4: Thermal characteristics

Symbol	Parameter	Conditions	Value	Unit
$R_{th(j-lead)}$	thermal resistance from junction to lead	full cycle	60	K/W
		half cycle	80	K/W
$R_{th(j-a)}$	thermal resistance from junction to ambient	mounted on a printed circuit board; lead length = 4 mm; Figure 1	150	K/W

7.1 Transient thermal impedance





Fig 1. Transient thermal impedance from junction to ambient as a function of pulse duration.

8. Characteristics

Table 5: Characteristics


$T_j = 25\text{ °C}$ unless otherwise specified

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static characteristics						
I_{GT}	gate trigger current	$V_D = 12\text{ V}$; $I_T = 0.1\text{ A}$; Figure 8				
		T2+ G+	–	1	5	mA
		T2+ G–	–	2	5	mA
		T2– G–	–	2	5	mA
		T2– G+	–	4	7	mA
I_L	latching current	$V_D = 12\text{ V}$; $I_{GT} = 0.1\text{ A}$; Figure 9				
		T2+ G+	–	1	10	mA
		T2+ G–	–	5	10	mA
		T2– G–	–	1	10	mA
		T2– G+	–	2	10	mA
I_H	holding current	$V_D = 12\text{ V}$; $I_{GT} = 0.1\text{ A}$; Figure 10	–	1	10	mA
V_T	on-state voltage	$I_T = 0.85\text{ A}$; Figure 11	–	1.4	1.9	V
V_{GT}	gate trigger voltage	$V_D = 12\text{ V}$; $I_T = 0.1\text{ A}$; Figure 7	–	0.9	2	V
		$V_D = V_{DRM}$; $I_T = 0.1\text{ A}$; $T_j = 110\text{ °C}$	0.1	0.7	–	V
I_D	off-state leakage current	$V_D = V_{DRM(max)}$; $T_j = 110\text{ °C}$	–	3	100	μA
Dynamic characteristics						
dV_D/dt	critical rate of rise of off-state voltage	$V_D = 67\%$ of $V_{DM(max)}$; $T_{case} = 110\text{ °C}$; exponential waveform; gate open circuit; Figure 12	30	45	–	$\text{V}/\mu\text{s}$
dV_{com}/dt	critical rate of rise of commutation voltage	$V_D = \text{rated } V_{DRM}$; $T_{case} = 50\text{ °C}$; $I_{TM} = 0.84\text{ A}$; commutating $di/dt = 0.3\text{ A/ms}$	–	5	–	$\text{V}/\mu\text{s}$
t_{gt}	gate controlled turn-on time	$I_{TM} = 1.0\text{ A}$; $V_D = V_{DRM(max)}$; $I_G = 25\text{ mA}$; $di_G/dt = 5\text{ A}/\mu\text{s}$	–	2	–	μs




α = conduction angle

Fig 2. Maximum on-state dissipation as a function of RMS on-state current; typical values.



$t_p \leq 20$ ms

Fig 3. Maximum permissible non-repetitive peak on-state current as a function of pulse width for sinusoidal currents; typical values.



n = number of cycles at $f = 50$ Hz

Fig 4. Maximum permissible non-repetitive peak on-state current as a function of number of cycles for sinusoidal currents; typical values.






Fig 5. Maximum permissible RMS current as a function of lead temperature; typical values.




$f = 50 \text{ Hz}; T_{\text{lead}} \leq 50 \text{ }^\circ\text{C}$

Fig 6. Maximum permissible repetitive RMS on-state current as a function of surge duration for sinusoidal currents; typical values.




$$a = \frac{V_{GT(T_j)}}{V_{GT(25^\circ\text{C})}}$$

Fig 7. Normalized gate trigger voltage as a function of junction temperature; typical values.




$$a = \frac{I_{GT(T_j)}}{I_{GT(25^\circ\text{C})}}$$

Fig 8. Normalized gate trigger current as a function of junction temperature; typical values.



$$a = \frac{I_{L(T_j)}}{I_{L(25^\circ\text{C})}}$$

Fig 9. Normalized latching current as a function of junction temperature; typical values.



$$a = \frac{I_{H(T_j)}}{I_{H(25^\circ\text{C})}}$$

Fig 10. Normalized holding current as a function of junction temperature; typical values.




Fig 11. On-state current as a function of on-state voltage; typical and maximum values.




Fig 12. Critical rate of rise of off-state voltage as a function of junction temperature; typical values.

9. Package outline

Plastic single-ended leaded (through hole) package; 3 leads

SOT54




Fig 13. SOT54 (TO-92).

10. Revision history

Table 6: Revision history

Rev	Date	CPCN	Description
01	20010329	-	Product specification; initial version

11. Data sheet status

Data sheet status ^[1]	Product status ^[2]	Definition
Objective data	Development	This data sheet contains data from the objective specification for product development. Philips Semiconductors reserves the right to change the specification in any manner without notice.
Preliminary data	Qualification	This data sheet contains data from the preliminary specification. Supplementary data will be published at a later date. Philips Semiconductors reserves the right to change the specification without notice, in order to improve the design and supply the best possible product.
Product data	Production	This data sheet contains data from the product specification. Philips Semiconductors reserves the right to make changes at any time in order to improve the design, manufacturing and supply. Changes will be communicated according to the Customer Product/Process Change Notification (CPCN) procedure SNW-SQ-650A.

[1] Please consult the most recently issued data sheet before initiating or completing a design.

[2] The product status of the device(s) described in this data sheet may have changed since this data sheet was published. The latest information is available on the Internet at URL <http://www.semiconductors.philips.com>.

12. Definitions

Short-form specification — The data in a short-form specification is extracted from a full data sheet with the same type number and title. For detailed information see the relevant data sheet or data handbook.

Limiting values definition — Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 60134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.

Application information — Applications that are described herein for any of these products are for illustrative purposes only. Philips Semiconductors make no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

13. Disclaimers

Life support — These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips Semiconductors customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips Semiconductors for any damages resulting from such application.

Right to make changes — Philips Semiconductors reserves the right to make changes, without notice, in the products, including circuits, standard cells, and/or software, described or contained herein in order to improve design and/or performance. Philips Semiconductors assumes no responsibility or liability for the use of any of these products, conveys no licence or title under any patent, copyright, or mask work right to these products, and makes no representations or warranties that these products are free from patent, copyright, or mask work right infringement, unless otherwise specified.

Philips Semiconductors - a worldwide company

Argentina: see South America

Australia: Tel. +61 2 9704 8141, Fax. +61 2 9704 8139

Austria: Tel. +43 160 101, Fax. +43 160 101 1210

Belarus: Tel. +375 17 220 0733, Fax. +375 17 220 0773

Belgium: see The Netherlands

Brazil: see South America

Bulgaria: Tel. +359 268 9211, Fax. +359 268 9102

Canada: Tel. +1 800 234 7381

China/Hong Kong: Tel. +852 2 319 7888, Fax. +852 2 319 7700

Colombia: see South America

Czech Republic: see Austria

Denmark: Tel. +45 3 288 2636, Fax. +45 3 157 0044

Finland: Tel. +358 961 5800, Fax. +358 96 158 0920

France: Tel. +33 1 4728 6600, Fax. +33 1 4728 6638

Germany: Tel. +49 40 23 5360, Fax. +49 402 353 6300

Hungary: Tel. +36 1 382 1700, Fax. +36 1 382 1800

India: Tel. +91 22 493 8541, Fax. +91 22 493 8722

Indonesia: see Singapore

Ireland: Tel. +353 17 64 0000, Fax. +353 17 64 0200

Israel: Tel. +972 36 45 0444, Fax. +972 36 49 1007

Italy: Tel. +39 039 203 6838, Fax. +39 039 203 6800

Japan: Tel. +81 33 740 5130, Fax. +81 3 3740 5057

Korea: Tel. +82 27 09 1412, Fax. +82 27 09 1415

Malaysia: Tel. +60 37 50 5214, Fax. +60 37 57 4880

Mexico: Tel. +9-5 800 234 7381

Middle East: see Italy

For all other countries apply to: Philips Semiconductors,
Marketing Communications,
Building BE, P.O. Box 218, 5600 MD EINDHOVEN,
The Netherlands, Fax. +31 40 272 4825

Netherlands: Tel. +31 40 278 2785, Fax. +31 40 278 8399

New Zealand: Tel. +64 98 49 4160, Fax. +64 98 49 7811

Norway: Tel. +47 22 74 8000, Fax. +47 22 74 8341

Philippines: Tel. +63 28 16 6380, Fax. +63 28 17 3474

Poland: Tel. +48 22 5710 000, Fax. +48 22 5710 001

Portugal: see Spain

Romania: see Italy

Russia: Tel. +7 095 755 6918, Fax. +7 095 755 6919

Singapore: Tel. +65 350 2538, Fax. +65 251 6500

Slovakia: see Austria

Slovenia: see Italy

South Africa: Tel. +27 11 471 5401, Fax. +27 11 471 5398

South America: Tel. +55 11 821 2333, Fax. +55 11 829 1849

Spain: Tel. +34 33 01 6312, Fax. +34 33 01 4107

Sweden: Tel. +46 86 32 2000, Fax. +46 86 32 2745

Switzerland: Tel. +41 14 88 2686, Fax. +41 14 81 7730

Taiwan: Tel. +886 22 134 2451, Fax. +886 22 134 2874

Thailand: Tel. +66 23 61 7910, Fax. +66 23 98 3447

Turkey: Tel. +90 216 522 1500, Fax. +90 216 522 1813

Ukraine: Tel. +380 44 264 2776, Fax. +380 44 268 0461

United Kingdom: Tel. +44 208 730 5000, Fax. +44 208 754 8421

United States: Tel. +1 800 234 7381

Uruguay: see South America

Vietnam: see Singapore

Yugoslavia: Tel. +381 11 3341 299, Fax. +381 11 3342 553

Internet: <http://www.semiconductors.philips.com>

(SCA72)

Contents

1	Description	1
2	Features	1
3	Applications	1
4	Pinning information	1
5	Quick reference data	2
6	Limiting values	2
7	Thermal characteristics	3
7.1	Transient thermal impedance	3
8	Characteristics	4
9	Package outline	8
10	Revision history	9
11	Data sheet status	10
12	Definitions	10
13	Disclaimers	10



PHILIPS

Let's make things better.

This datasheet has been download from:

www.datasheetcatalog.com

Datasheets for electronics components.