



Technical Data Sheet

5484/Y3DC-AHLC/X/MS

Features

- High luminous intensity output
- Oval Shape
- Well defined spatial radiation
- Wide viewing angle ($2\theta_{1/2}$) : $100^\circ / 40^\circ$
- UV resistant epoxy
- The product itself will remain within RoHS compliant version



Descriptions

- This precision optical performance oval LED is specifically designed for passenger information signs
- This lamp has matched radiation patterns with red mixing dual color applications
- Superior performance in outdoor environment

Applications

- Color graphic signs
- Message boards
- Variable message signs (VMS)
- Commercial outdoor advertising



Device Selection Guide

| LED Part No. | Chip Material | Emitted Color | Lens Color | Stopper |
|---------------------|---------------|---------------|-----------------|---------|
| 5484/Y3DC-AHLC/MS | AlGaInP | Super Yellow | Yellow Diffused | No |
| 5484/Y3DC-AHLC/P/MS | | | | Yes |

Package Dimensions

Stopper Type

No Stopper Type



Notes:

- Other dimensions are in millimeters, tolerance is 0.25mm except being specified.
- Protruded resin under flange is 1.5mm Max LED.
- Bare copper alloy is exposed at tie-bar portion after cutting.



Technical Data Sheet

5484/Y3DC-AHLC/X/MS

Absolute Maximum Rating ($T_a=25^{\circ}\text{C}$)

| Parameter | Symbol | Absolute Maximum Rating | Unit |
|---|-----------|-------------------------|--------------------|
| Forward Current | I_F | 50 | mA |
| Pulse Forward Current (Duty1/10@ 1KHz) | I_{FP} | 160 | mA |
| Operating Temperature | T_{opr} | -40 ~ +85 | $^{\circ}\text{C}$ |
| Storage Temperature | T_{stg} | -40 ~ +100 | $^{\circ}\text{C}$ |
| Soldering Temperature(Notes *1) | T_{sol} | 260 \pm 5 | $^{\circ}\text{C}$ |
| Power Dissipation | P_d | 120 | mW |
| Reverse Voltage | V_R | 5 | V |

Notes *1: Soldering time \leq 5 seconds.

Electro-Optical Characteristics ($T_a=25^{\circ}\text{C}$)

| Parameter | Symbol | Min. | Typ. | Max. | Unit | Condition |
|---------------------|-----------------|------|-----------|------|---------------|-------------------|
| Luminous Intensity | I_V | 715 | 1100 | 1800 | mcd | $I_F=20\text{mA}$ |
| Viewing Angle | $2\theta_{1/2}$ | -- | X:100Y:40 | -- | deg | |
| Peak Wavelength | λ_p | -- | 591 | -- | nm | |
| Dominant Wavelength | λ_d | 584 | 589 | 596 | | |
| Spectrum Half width | $\Delta\lambda$ | -- | 15 | -- | | |
| Forward Voltage | V_F | 2.0 | 2.3 | 2.6 | V | $V_R=5\text{V}$ |
| Reverse Current | I_R | -- | -- | 10 | μA | |

Rank Combination ($I_F=20\text{mA}$)

| Rank | H | J | K | L |
|--------------------|---------|----------|-----------|-----------|
| Luminous Intensity | 715~900 | 900~1125 | 1125~1425 | 1425~1800 |

*Measurement Uncertainty of Luminous Intensity: $\pm 15\%$

Unit:mcd

| Rank | 2 | 3 | 4 |
|-----------------|---------|---------|---------|
| Forward Voltage | 2.0~2.2 | 2.2~2.4 | 2.4~2.6 |

*Measurement Uncertainty of Forward Voltage: $\pm 0.1\text{V}$

Unit:V







| Rank | 1 | 2 | 3 | 4 |
|---------------------|---------|---------|---------|---------|
| Dominant Wavelength | 584~587 | 587~590 | 590~593 | 593~596 |

*Measurement Uncertainty of Dominant Wavelength $\pm 1.0\text{nm}$

Unit:nm

*The quantity ratio of the ranks is decided by EVERLIGHT.

Typical Electro-Optical Characteristics Curves





Technical Data Sheet

5484/Y3DC-AHLC/X/MS

Packing Quantity Specification

1.500PCS/1Bag , 5Bags/1Box

2.10Boxes/1Carton

Label Form Specification

| | |
|---|---|
| EVERLIGHT | |
| CPN: | |
| P/N: | |
|  |  |
| 5484/Y3DC-AHLC/X/MS | |
| QTY : | CAT: |
|  | HUE: |
| LOT NO : | REF: |
|  | |
| MADE IN TAIWAN | |

CPN: Customer's Production Number

P/N : Production Number

QTY: Packing Quantity

CAT: Ranks of Luminous Intensity and Forward Voltage

HUE: Ranks of Dominant Wavelength

REF: Reference

LOT No: Lot Number

MADE IN TAIWAN: Production Place



Technical Data Sheet

5484/Y3DC-AHLC/X/MS

Notes

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. When using this product, please observe the absolute maximum ratings and the instructions for using outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
3. These specification sheets include materials protected under copyright of EVERLIGHT corporation. Please don't reproduce or cause anyone to reproduce them without EVERLIGHT's consent.
4. Soldering Condition

Careful attention should be paid during soldering. When soldering, leave more than 3mm from solder joint to case, and soldering beyond the base of the tie bar is recommended.

Avoiding applying any stress to the lead frame while the LEDs are at high temperature particularly when soldering.

Recommended soldering conditions:

| Hand Soldering | | DIP Soldering | |
|----------------------|-------------------------------------|---------------|--------------------------|
| Temp. at tip of iron | 400°C Max. (30W Max.) | Preheat temp. | 100°C Max. (60 sec Max.) |
| Soldering time | 3 sec Max. | Bath temp. | 265 Max. |
| Distance | 3mm Min.(From solder joint to case) | Bath time. | 5 sec Max. |
| | | Distance | 3mm Min. |

EVERLIGHT ELECTRONICS CO., LTD.
Office: No 25, Lane 76, Sec 3, Chung Yang Rd,
Tucheng, Taipei 236, Taiwan, R.O.C

Tel: 886-2-2267-2000, 2267-9936
Fax: 886-2267-6244, 2267-6189, 2267-6306
<http://www.everlight.com>