

The figure is a technical drawing of a magnetic buzzer, labeled KP12-04F1. It includes three views: a top view, a side view, and a cross-sectional view. The top view shows a circular component with a diameter of 13.4 ± 0.2 mm and a central pin with a diameter of 2.0 ± 0.05 mm. The side view shows a cylindrical body with a height of 5.7 ± 0.2 mm and a base diameter of 6.0 ± 0.3 mm. The cross-sectional view shows the internal components, including a coil and a magnet, with a total height of 5.0 ± 0.5 mm and a base diameter of 6.5 ± 0.2 mm.

SPECIFICATION

1. Rated Voltage.....	1.5V
2. Operating Voltage.....	1-2V
3. Max. Rated Current.....	70mA
4. Coil Resistance.....	5±1Ω
5. Coil Impedance	15Ω
6. Min. Sound Pressure Level.....	85dB/10cm
7. Resonant Frequency.....	2731Hz
8. Case Material.....	MPP0
9. Operating Temperature.....	-20~+70℃
10. Store Temperature.....	-30~+80℃
11. Weight.....	2g

KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com			
No.	DESCRIPTION	APPROVED	DATE
Magnetic buzzer KP12-04F1		DATE	
DRAWN		CHECKED	UNIT
APPROVED		APPROVED	mm
05.08.01		SCALE	NOT TO SCALE
SHEET		VTR 1.0	

[illegible]