

规格书编号

SPEC NO :

# 产品规格书

# SPECIFICATION

CUSTOMER 客 户 : \_\_\_\_\_

PRODUCT 产 品 : \_\_\_\_\_ CRYSTAL FILTER \_\_\_\_\_

MODEL NO 型 号 : \_\_\_\_\_ UM-1-55.845M20A \_\_\_\_\_

PREPARED 编 制 : \_\_\_\_\_ Chenqinggui \_\_\_\_\_ CHECKED 审 核 : \_\_\_\_\_ york \_\_\_\_\_

APPROVED 批 准 : \_\_\_\_\_ Wangjianwen \_\_\_\_\_ D A T E 日 期 : \_\_\_\_\_ 2010-9-2 \_\_\_\_\_

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子有限公司

Shoulder Electronics Limited



## 更改历史记录

## History Record

[illegible]

## 1. SPECIFICATION

<div> <div>□ APPLICATION</div> <p>This Standard Will Apply to The Quartz Crystals.</p> <div>□ ELECTRICAL DATA</div> </div>		
NO	Speciality	Parameter
01	Holder type	UM-1-55.845M20A
02	Mode of Oscillations	Fundamental
03	Center Frequency	55.845MHz
04	Pass bandwidth	$\pm 10\text{KHz}$ min (at 3dB)
05	Pass band ripple	0.5dB max
06	Insertion loss	1.5dB max
07	Stop Band width	$\pm 40\text{KHz}$ max (at 20dB)
08	Terminating impedance	$3600\Omega // 0.8\text{pf}$
09	Operating Tem. Range	$-20 \sim +70^{\circ}\text{C}$
10	Insulated Resistance	$500\text{M}\Omega(\text{max})(\text{DC}100\text{V})$
11	Aging per Year	$\pm 3\text{ppm}$

## 2. MECHANICAL DATA

1. Marking :	<div style="border: 1px solid black; padding: 10px; text-align: center;"> <p>SDE</p> <p>55M20A</p> </div>
2. Shock Test :	Dropping from 75 cm height, 3 times on 30mm-thick- hard wood, After testing, the electrical data follows the requirement.
3. Vibration Test :	30 minutes in each direction 10 to 55 Hz, amplitude 0.75mm, After testing, the electrical data follows the requirement.
4. Terminal strength :	<p>Tensile: Fix main body of crystal. Load 0.9kg pulling force along, terminal axial for 30±5 seconds.</p> <p>The terminal can not be pulled out or broken.</p> <p>Bending: Hang 450g object on lead terminal. Bend 90 degree for 2 to 3 seconds. Return to the former place with the same speed and then do it again oppositely. The down-lead does not become broken and loosed.</p>
5. Sealing :	The crystal unit shall be immersed in alcohol for 5 minutes with 5kg pressure per cm <sup>2</sup> . Taking out, Testing the resistance between down-lead and fundamental. The resistance shall be at least 500MΩ(max) (DC100V).
6. Temperature cycle :	<p>2 ~ 3 min    -20°C to +70°C</p> <p>30min    30min</p> <p>After cycling three times, there is no distinct damage on the surface.</p> <p>Capacity testing requirement as vibration.</p>
7. Solderability :	<p>The lead(2to2.5mm from terminal to bottom) is immersed in a 230±5°C Solder bath within 2±0.5 seconds.</p> <p>The dipping surface of the lead shall be at least 95% covered with a Continuous new solder coating.</p> <p>Capacity testing requirement as vibration.</p>

8. Resistance to soldering heat :	The(2 to 2.5mm from terminal to bottom) is immersed in a $350\pm 10^{\circ}\text{C}$ solder bath within $3.5\pm 0.5$ seconds. After testing, without distinct damage on the surface. Capacity testing requirement as vibration.
9. Resistance to heat :	Resistance to the lowest temperature: Stored at $-25\pm 3^{\circ}\text{C}$ for 2 hours and then at normal temperature for 2 hours before testing. Capacity testing requirement as vibration. Resistance to the highest temperature: Stored at $70\pm 2^{\circ}\text{C}$ for 2 hours and then at normal temperature for 2 hours before testing. Capacity testing requirement as vibration.
10. Invariable humidity :	Stored at $40\pm 3^{\circ}\text{C}$ and $\text{RH}93\%\pm 2\%$ for 48 hours and then at normal condition for 2 hours before testing. Without distinct damage to the surface. Capacity testing requirement as vibration.

### 3. DIMENSIONS

