

规格书编号

SPEC NO :

产品规格书

SPECIFICATION

CUSTOMER 客 户 : _____

PRODUCT 产 品 : _____ SAW FILTER _____

MODEL NO 型 号 : _____ HDF1575A SMD-6 _____

PREPARED 编 制 : _____ CHECKED 审 核 : _____

APPROVED 批 准 : _____ D A T E 日 期 : _____ 2006-5-11 _____

客户确认 CUSTOMER RECEIVED:		
审核 CHECKED	批准 APPROVED	日期 DATE

无锡市好达电子股份有限公司
Shoulder Electronics Limited

更改历史记录

History Record

[illegible]

1.Features


GPS applications

Usable bandwidth of 2 MHz

No impedance matching require for operation at 50 .

Single-ended Operation

2.Package Dimension



3. Marking

- 2.1 Color: Black or Blue
- 2.2 1575: Center Frequency(MHz)

4. Performance


4.1 Application

Low-Loss SAW Filter of cordless system.
Center Frequency:1575.42 MHz

4.2 Maximum Rating

Operation Temperature Range	-40°C to +85°C
Storage Temperature Range	-40°Cto +85°C
Power Handling Capability	10dBm

4.3 Electronic Characteristics




Parameter	Symbol	Conditions	Min	Typ.	Max.	Unit
Center frequency				1575.42		MHZ
Operational bandwidth	f op		1574.22		1576.62	MHz
Insertion Loss	IL	In f op		1.5	2.5	dB
Amplitude Variation	AV	In f op		0.2	0.5	dB
VSWER	SWR	In f op		1.3	2	
Rejectiona wrt 0 dB	Rj1	0.3 ~ 700 MHz	40	45		dB
In Top	Rj2	700~1460MHz	37	40.5		dB
	Rj3	1460~1470MHz	45	50		dB
	Rj4	1470~1525MHz	37	43		dB
	Rj5	1525~1535.42MHz	20	25		dB
	Rj6	1615.42~1620MHz	25	35		dB
	Rj7	1620~1650 MHz	45	50		dB
	Rj8	1650~3000 MHz	40	45		dB
I/P & O/P impedance	Zin/Zout	Unmatched		50		Ohm

Notes :

- 1) All specifications are based on the matching schematic shown below, measured by Agilent Network analyzer and full 2 port calibration.
- 2) Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances
- 3) All attenuation measurements are measured relative to insertion loss

4.4 Test Circuit



5. ENVIRONMENTAL CHARACTERISTICS

5-1 Temperature cycling

Subject the device to a low temperature of -40°C for 30 minutes. Following by a high temperature of $+25^{\circ}\text{C}$ for 5 Minutes and a higher temperature of $+85^{\circ}\text{C}$ for 30 Minutes. Then release the device into the room conditions for 1 to 2 hours prior to the measurement. It shall meet the specifications in table 1.

5-2 Resistance to solder heat

Submerge the device terminals into the solder bath at $260^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 10 ± 1 sec. Then release the device into the room conditions for 4 hours. It shall meet the specifications in table 1.

5-3 Solderability

Submerge the device terminals into the solder bath at $245^{\circ}\text{C} \pm 5^{\circ}\text{C}$ for 5s, More than 95% area of the soldering pad must be covered with new solder. It shall meet the specifications in table 1.

5-4 Mechanical shock

Drop the device randomly onto the concrete floor from the height of 1 m 3 times. the filter shall fulfill the specifications in table 1.

5-5 Vibration

Subject the device to the vibration for 2 hour each in x,y and z axes with the amplitude of 1.5 mm at 10 to 55 hz. The filter shall fulfill the specifications in table 1.

6. REMARK

6.1 Static voltage

Static voltage between signal load & ground may cause deterioration & destruction of the component. Please avoid static voltage.

6.2 Ultrasonic cleaning

Ultrasonic vibration may cause deterioration & destruction of the component. Please avoid ultrasonic cleaning

6.3 Soldering

Only leads of component may be soldered. Please avoid soldering another part of component.

7. Packing

7.1 Dimensions


- (1) Carrier Tape: Figure 1
- (2) Reel: Figure 2
- (3) The product shall be packed properly not to be damaged during transportation and storage.

7.2 Reeling Quantity

1000 pcs/reel 7"
3000 pcs/reel 13"

7.3 Taping Structure


- (1) The tape shall be wound around the reel in the direction shown below.




- (2) Label

Device Name	
User Product Name	
Quantity	
Lot No.	

- (3) Leader part and vacant position specifications.



[Unit:mm]



A	B	C	D	E	W	t	r
Ø330	Ø100	Ø13	Ø21	2	13	3	1.0
±1.0	±0.5	±0.5	±0.8	±0.5	±0.3	max.	max.