



PRODUCT INFORMATION

PART #

BS-IC

Revision: 1-2013

9 V Cell Connector, PVC Vinyl, "I" Style



ISO 9001

SPECIFICATIONS






Battery (Cell) Type	9V		Number of Cells	1	
Cell Configuration	Series Connection		Output Voltage	9 Vdc	
Operating Temperature	-20°C to + 65°C		Storage Temperature	-30°C to +85°C	
Material	Case	PCV Vinyl, Black		Washer	
	Contact	6 Prongs Snap Terminal			
	Termination	Wire Leads, 26 AWG, UL 1007, Stranded, 150 ± 5 mm, Stripped and Tinned 5 ± 1 mm			
Physical Dimensions	Length (L)	28 mm	Width (W)	14.5 mm	Height (H) 6.8 mm
Approximate Weight	grams		Compliance	RoHS	
Options					

RELIABILITY

Insulation Test	A minimum of 10 MΩ, measured with 100 Vdc Insulation Resistance Meter, between the Electrical Terminals and the Case
Vibration Test	2 Hours of at 1.5 mm with 10 to 55 Hz. vibration frequency to each of 3 perpendicular directions
Termination Strength	Maximum of 9.8 N (1.0 Kg) load pull test, applied to each terminal in axial direction for 10 seconds
Drop Test	Dropped naturally from 750 mm height onto the surface of 40 mm wooden board, 3 axes (X,Y,Z) directions, 3 times (6 times total)
Warranty	For a period of one (1) year from date of shipping under normal operations conditions

DIMENSIONS

Dimensions in mm; Tolerance ±0.5 mm



Revision	Description	By	Date
1-2013	Corrected case material from ABS Resin to PVC Vinyl	Walter Sargent	11/18/2013

The information contained herein is believed to be correct, but no guarantee or warranty, express or implied, with respect to accuracy, completeness or results is extended and no liability is assumed. Challenge Electronics reserves the right to make changes in any specification, data or material contained herein.

Copyright © 2012 Challenge Electronics



Challenge Electronics
95 East Jefryn Boulevard
Deer Park, NY 11729

Tel: 1-800-722-8197
1-631-595-2217
Fax: 1-631-667-5484

EMAIL: SALES@CHALLELEC.COM
WEB:
WWW.CHALLENGEELECTRONICS.COM