

multicomp	PART NO.		REVISIONS								
	CH74-2032LF	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE	
		-	А	RELEASED	Asha	26/11/11	Veena	26/11/11		10/12/11	





6.4



"-" Electrode 1.5 3.4 4 യി 3 × Ø1.3 10 Holes 13.1

Specifications:

Material:


Housing Contact


Current rating Voltage rating Contact resistance Insulation resistance Temperature range Humidity



: Nylon 46 + 30% GF Black colour : Phosphor bronze 0.6 mm thick Tin plated over nickel : 3 A ac / dc : 500 V ac / dc : 12 mΩ : 500 MΩ : -40°C to +105°C

: 40°C and 90 - 95% RH for 96 hrs





- Andrewson -	 	-	

General Tolerance						
Dimension : 0	±0.3					
0	±0.2					
Angle : ±3° 0	±0.1					

PCB Mounting Layout

Dimensions : Millimetres

www.element14.com

www.farnell.com

www.newark.com

licence is granted for the use of it other than for information purposes in connection with	TOLERANCES: UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	DRAWN BY: Asha	DATE: 26/11/11	DRAWING TITLE:	Battery Ho	lder	
use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on		CHECKED BY: Veena	DATE: 26/11/11	SIZE DWG NO.	M10002771	ELECTRONIC FILE CH 74-2032LF_DWG	REV A
		APPROVED BY:	DATE: 10/12/11	SCALE: NTS	U.O.M.: mm	SHEET: 1 OF	- 1

Part Number Table

Description	Part Number
Battery Holder, DIP, Vert, 20 mm	CH74-2032LF