

CPC1017N

4 Pin SOP OptoMOS® Relays



| | CPC1017N | Units |
|--------------------|----------|----------|
| Load Voltage | 60 | V |
| Load Current | 100 | mA |
| Max R_{ON} | 16 | Ω |
| Current to operate | 1.0 | mA |

Features

- Design for use in security systems complying with EN50130-4
- Only 1mA of LED current required to operate
- Small 4 Pin SOP Package
- TTL/CMOS Compatible input
- No Moving Parts
- High Reliability
- Arc-Free With No Snubbing Circuits
- 1500V_{RMS} Input/Output Isolation/2100V AC peak
- No EMI/RFI Generation
- Immune to radiated EM fields
- SMD Pick & Place, Wave Solderable
- Tape & Reel Version Available

Applications

- Security
 - Passive Infrared Detectors (PIR)
 - Data Signalling
 - Sensor Circuitry
- Instrumentation
 - Multiplexers
 - Data Acquisition
 - Electronic Switching
 - I/O Subsystems
 - Meters (Watt-Hour, Water, Gas)
- Medical Equipment—Patient/Equipment Isolation
- Aerospace
- Industrial Controls

Description

The CPC1017N is a miniature 1-Form-A solid state relay in a 4 pin SOP package that employs optically coupled MOSFET technology to provide 1500V of input to output isolation. The super efficient MOSFET switches and photovoltaic die use Clare's patented OptoMOS architecture. The optically coupled input is controlled by a highly efficient GaAlAs infrared LED. The CPC1017N uses Clare's state-of-the-art double molded vertical construction packaging to produce the world's smallest relay. The CPC1017N offers board space savings of at least 20% over the competitor's larger 4 pin SOP relay. It boasts the industries' lowest input current to operate in its class.

Approvals


- UL Recognized Component
- BSI Certified to EN60950

Ordering Information


| Part # | Description |
|------------|------------------------|
| CPC1017N | 4 Pin SOP (100/tube) |
| CPC1017NTR | 4 Pin SOP (2,000/reel) |

Pin Configuration

CPC1017N Pinout



Switching Characteristics of Normally Open (Form A) Devices



CPC1017N

Absolute Maximum Ratings (@ 25° C)

| Parameter | Min | Typ | Max | Units |
|---|------|-----|------------------|-------------------|
| Input Power Dissipation | - | - | 70 | mW |
| Input Control Current | - | - | 50 | mA |
| Peak (10ms) | - | - | 1 | A |
| Reverse Input Voltage | - | - | 5 | V |
| Total Power Dissipation | - | - | 400 ¹ | mW |
| Isolation Voltage Input to Output(AC Peak test voltage) | 2100 | - | - | V _{peak} |
| Operational Temperature | -40 | - | +85 | °C |
| Storage Temperature | -40 | - | +125 | °C |
| Soldering Temperature (10 Seconds Max.) | - | - | +220 | °C |

¹ Derate Linearly 3.33 mw / °C

Absolute Maximum Ratings are stress ratings. Stresses in excess of these ratings can cause permanent damage to the device. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and effect its reliability.

Electrical Characteristics

| Parameter | Conditions | Symbol | Min | Typ | Max | Units |
|---|--|-------------------|-----|-----|-----|-------|
| Output Characteristics @ 25°C | | | | | | |
| Load Voltage (Peak) | I _L =1μA | V _L | - | - | 60 | V |
| Load Current (Continuous) AC Peak ¹ | I _F =10mA | I _L | - | - | 100 | mA |
| Peak Load Current | 10ms | I _{LPK} | - | - | 350 | mA |
| On-Resistance ² | I _L =100mA | R _{ON} | - | - | 16 | Ω |
| Off-State Leakage Current | V _L =60V | I _{LEAK} | - | - | 1 | μA |
| Switching Speeds | | | | | | |
| Turn-On | I _F =5mA, V _L =10V | T _{ON} | - | - | 10 | ms |
| Turn-Off | I _F =5mA, V _L =10V | T _{OFF} | - | - | 10 | ms |
| Output Capacitance | 50V; f=1MHz | C _{OUT} | - | 25 | - | pF |
| Capacitance Input to Output | - | - | - | 1 | - | pF |
| Input Characteristics @ 25°C | | | | | | |
| Input Control Current ³ | I _L =150mA | I _F | 1 | - | 50 | mA |
| Input Dropout Current | - | I _F | 0.3 | 0.9 | - | mA |
| Input Voltage Drop | I _F =5mA | V _F | 0.9 | 1.2 | 1.4 | V |
| Reverse Input Voltage | - | V _R | - | - | 5 | V |
| Reverse Input Current | V _R =5V | I _R | - | - | 10 | μA |

¹Load current derates linearly from 100mA @ 25°C to 80mA @ 80°C.

² Measurement taken within 1 second of on time.

³ For applications requiring high temperature operation (greater than 60°C) an LED drive current of 3mA is recommended.