



10A05G THRU 10A10G

硅整流二极管 General Purpose Rectifier


■特征 Features

- I_o 10A
- VRRM 50V-1000V
- 耐正向浪涌电流能力高
- High surge current capability

■用途 Applications

- 整流用 Rectifier

■外形尺寸和印记 Outline Dimensions and Mark



■极限值（绝对最大额定值）

Limiting Values (Absolute Maximum Rating)

参数名称 Item	符号 Symbol	单位 Unit	条件 Conditions	10A						
				05G	1G	2G	4G	6G	8G	10G
反向重复峰值电压 Repetitive Peak Reverse Voltage	V_{RRM}	V		50	100	200	400	600	800	1000
正向平均电流 Average Forward Current	$I_{F(AV)}$	A	正弦半波 60Hz, 电阻负载, $T_a=50^{\circ}\text{C}$ 60Hz Half-sine wave, Resistance load, $T_a=50^{\circ}\text{C}$	10						
正向（不重复）浪涌电流 Surge(Non-repetitive)Forward Current	I_{FSM}	A	正弦半波 60Hz, 一个周期, $T_a=25^{\circ}\text{C}$ 60Hz Half-sine wave, 1 cycle, $T_a=25^{\circ}\text{C}$	600						
结温 Junction Temperature	T_J	$^{\circ}\text{C}$		-55~+150						
储存温度 Storage Temperature	T_{STG}	$^{\circ}\text{C}$		-55 ~ +150						

■电特性（ $T_a=25^{\circ}\text{C}$ 除非另有规定）

Electrical Characteristics ($T_a=25^{\circ}\text{C}$ Unless otherwise specified)

参数名称 Item	符号 Symbol	单位 Unit	测试条件 Test Condition	最大值 Max
正向峰值电压 Peak Forward Voltage	V_{FM}	V	$I_{FM}=10\text{A}$	1.1
反向峰值电流 Peak Reverse Current	I_{RRM1}	μA	$V_{RM}=V_{RRM}$	$T_a=25^{\circ}\text{C}$ 2.5
	I_{RRM2}			$T_a=125^{\circ}\text{C}$ 100
热阻(典型) Thermal Resistance(Typical)	$R_{\theta JA}$	$^{\circ}\text{C}/\text{W}$	结和环境之间 Between junction and ambient	20
结电容 Typical junction capacitance	C_j	pF	Measured at 1MHZ and Applied Reverse Voltage of 4.0 V.D.C.	150

■特性曲线（典型） Characteristics(Typical)

