

PRODUCT SPECIFICATION

Model No.: FYL-3017EGW1A

Descriptions:
■ Dice material: GaP/ GaP
■ Emitting Color: Orange/Yellow green
■ Device Outline: Φ3mm round type.
■ Lens Type: White Diffused



CUSTOMER APPROVED SIGNATURES	APPROVED BY	CHECKED BY	PREPARED BY

NINGBO FORYARD OPTOELECTRONICS CO.,LTD.

Add: NO.115 Qixin Road Ningbo Zhejiang China

Zip: 315051

Tel: 0086-574-87933652 87927870 87922206

Fax: 0086-574-87927917


E-mail: Sales@foryard.com (General)

[Http://www.foryard.com](http://www.foryard.com)

■ Features

1. Low power consumption.
2. High efficiency.
3. General purpose leads.
4. RoHs compliant.

■ Package configuration



Notes:

1. All dimensions are millimeters (inches)
2. Tolerance is $\pm 0.25\text{mm}$ (.010") unless otherwise noted.
3. The specifications, characteristics and technical data described in the datasheet are subject to change without prior notice.

■ Absolute maximum ratings($T_a=25\text{ }^{\circ}\text{C}$)


Parameter	MAX.	Unit
Power Dissipation	E 75	mW
	G 75	
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	30	mA
Derating Linear From 50°C	0.4	mA/°C
Reverse Voltage	5	V
Operating Temperature Range	-40°C to +85°C	
Storage Temperature Range	-40°C to +100°C	
Lead Soldering Temperature[4mm(.157") From Body]	260°C for 5 Seconds	

■ Electrical and optical characteristics($T_a=25\text{ }^{\circ}\text{C}$)


Parameter	Symbol		Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I _v	E	—	20	—	mcd	I _F =20mA
		G		30			
Viewing Angle	2θ _{1/2}	E	—	50	—	Deg	
		G		50			
Peak Emission Wavelength	λ _p	E	620	625	630	nm	
		G	563	568	573		
Dominant Wavelength	λ _d	E	615	620	625	nm	
		G	567	572	577		
Spectral Line Half-Width	△λ	E	10	15	20	nm	
		G	15	20	25		
Forward Voltage	V _F	E	1.8	2.0	2.4	V	
		G	1.8	2.3	2.5		
Reverse Current	I _R				10	μA	V _R =5V

■ Typical Electrical Characteristics Curves


(25 °c Ambient Temperature Unless Otherwise Noted)





Radiation pattern.



■ LAMP PACKING.



3mm 1000PCS/Polybag



72000PCS/ Carton



OUTSIDE LABEL