



- Part No:CXS1-XXXXXXXX-AXXB12, eg. CXS1-01200000-A125BA12
- Used for Quartz Clock, Time-Counter in Computer, Monitor System in Airplane、Train etc
- Low Cost and High Stability

PARAMETERS:

ITEM	MIN	MAX	UNIT
Frequency Range	3.5	60.000	MHz
Vibration Mode	AT-Cut, fundamental, 3rd		
Frequency Tolerance @ 25°C ±2°C	±10	±50	ppm
Operation Temperature	-20°C~+70°C		
Frequency Stability	±30(-10°C~+60°C)		ppm
Store Temperature	-40~+85°C		
Resonance resistance	30	150	Ω
Shunt Capacitance	7(max)		PF
Drive Level	100		μW
Load Capacitance	12~50PF or Series		PF
Insulation Resistance	500MΩ/DC:100±15V		

Figure:



Dimension: Unit: mm





Table1: resonance resistance

FREQUENCY RANGE/MHz	vibration	Rr (Ω)
3.2~3.99MHz	Fund	150
4.0~4.99MHz	Fund	120
5.0~5.99MHz	Fund	100
6.0~6.99MHz	Fund	80
7.0~7.99MHz	Fund	60
4.5~5.0MHz	Fund	60
10.0~13.99MHz	Fund	50
14.0~19.99MHz	Fund	40
20.0~40.0MHz	Fund	25
25.0~40.0MHz	3rd Overtone	100
40.0~100.0MHz	5rd Overtone	80

Table 2:Operation Temperature and Tolerance

Temperature Range	Frequency Stability	
	MIN	MAX
0°C~+50°C	±2.5PPM	±100PPM
-10°C~+60°C	±10PPM	±100PPM
-20°C~+70°C	±10PPM	±100PPM
-30°C~+80°C	±15PPM	±100PPM
-40°C~+85°C	±20PPM	±100PPM

Application Chart:

