

# Anhui Safe Electronics Co.,LTD.

## CBB65A Capacitor Data.

### CBB65 AC Capacitor

\* Capacitance Range:3UF-100UF

\* Capacitance range: 5%,10%

\* Rated Voltage:AC250V-630V

### CBB65 AC Capacitor

Feature:

The product is equipped inside with reliable explosion-proof equipment and is highly safe. With its good self-healing characteristic and long life-span, it is widely used for air-conditioners, refrigerators, generators, compressor, etc..

Specification:

Working Temperature Range climate types: 40/70/21

Rated Voltage Range 250Vac, 300Vac, 370Vac, 440Vac ,500Vac,630Vac

Rated Capacitance Range 3-100uF

Dissipation Factor Tan  $\leq$  0.002 (50Hz)

Rated Tolerance of capacitance 5% 10%

Testing Voltage between leading-out ends: 1.75UR 10S no break down

Insulation resistance between leading-out ends: 3000

Product Type	Metallized Film Capacitor
Capacitance Range	3UF~120UF
Capacitance Deviation	$\pm$ 5% or According to Customer's requests.
Rated Voltage	200VAC,250VAC,370VAC,400VAC,440VAC, 500VAC,550VAC,630VAC,660VAC

Rated Frequency		50/60Hz	
Class of safety protection		P1/P2	
Testing Voltage		T-T:2.0Un/60S	
Insulation Resistance		≥3000S	
Tangent of loss angle of a capacitor		Tan δ ≤0.002(100Hz)	
Operating Temperature		-40° C~+85 ° C	
Life Span		Class B, Class C	
Rated Volatge (VAC)	Nominal Capacitance Microfarad (uF)	Dimention (mm)	
		Diameter	Height
200VAC,250VAC, 370VAC,400VA C,	3,4,5,7.5,10,12.5,15,17 ,		60,65,70.75
440VAC,450VAC, 500VAC,550VA C,	20,22.5,25,30,35,40, 45, 50,55, 60,70,80,100,120	40,45,50,55 60,63.5 52*32,71*48.5	80,85,90,95 100,105,110 115,120,125
630VAC,660VAC	25+5,30+5,35+5,50+5, 60+5,70+5,80+5....		135,138

