



SPECIFICATION

1. Rated Voltage 9Vp-p Square Wave
2. Max Allowable Voltage 30Vp-p Square Wave
3. Max. Rated Current 5mA at 1.4KHz/9Vp-p Square Wave
4. Resonant Frequency 1.4±0.5KHz
5. Min. Sound Pressure Level..... 85dB at 1.4KHz/9Vp-p Square Wave/10cm
6. Capacitance at 120Hz 50000pF±30%
7. Case Material ABS
8. Operating Temperature -20~+60℃
9. Store Temperature -30~+70℃
10. Weight 6g

No.		DESCRIPTION		APPROVED		DATE	
<small>DESIGN/ENGINEER'S SIGNATURE</small>		<small>APPROVALS</small>					
<small>NORTH OVIOTRONIC</small>		<small>DATE</small>					
<small>X ±</small>		<small>DRAWN</small>					
<small>XX ±</small>		<small>CHECKED</small>					
<small>90° ±</small>		<small>APPROVED</small>					
<small>THESE ANGLES INDICATION</small>							
<div style="display: flex; justify-content: space-between; align-items: center;"> <div style="text-align: center;">  <p>THIRD ANGLE PROJECTION</p> </div> <div style="text-align: center;">  </div> </div>				04.05.07		SCALE	
				UNIT		DWG. NO.	
				mm		OEM1038	
				APPROVED		SHEET	
						VER. 1.1	

KEPO NINGBO KEPO ELECTRONIC CO.,LTD
<http://www.chinaacoustic.com>

Piezo transducer
CBE3514BL
 大洋