



Scop. This specification is only used for mechanical buzzer

| Items | Specifications |
|---------------------------|--------------------|
| Rated Voltage | 12VDC |
| Operating Voltage | 9 ~ 15VDC |
| Max. Rated Current | 30mA/12VDC |
| Response Time | 50ms |
| Tone Nature | / |
| Min. Sound Pressure Level | 80dB at 12VDC/20cm |
| Resonant Frequency | 400 ± 100Hz |
| Shell Material/Color | ABS/White |
| Operating Temperature | -20 ~ +60 |
| Store Temperature | -30 ~ +70 |
| Weight | 10g |

| | | | | |
|--|--------------|--|---|--|
| FIRST ANGLE PROJECTION  | CUSTOMER | |  TEL:(+86)574-88370330 FAX:(+86)574-88370329 Http://www.chinaacoustic.com Ningbo Keep Improving Electronics Co. Ltd. | |
| | W&M | | | |
| TOLERANCES UNLESS NOTED OTHERWISE .X ± .XX ± .XXX ± 90° FORMED +2° ANGLES -1° | CUSTOMER NO. | | KEPO MODEL NO. | |
| | DRAWN | | 02.06.24 | |
| | QA. | | REV. 1.0 | |
| | PROJ. | | SHEET | |
| | | | DWG NO. | |
| | | | OEM188 | |