



这类振荡器采用具有高密封性能的蜂焊，以达到薄化，超小型化。应用于数码相机、摄像系统、硬盘、无线网卡、卫星定位、掌上电脑等。

This Oscillator is SMD package, miniature and of high accuracy. It's widely used in Communication Equipment, Digital Camera, wireless NIC, GPS, HDD, PDA etc.

技术参数 SPECIFICATIONS

频率范围	FREQUENCY RANGE	1MHz~75MHz
存储温度范围	STORAGE TEMPERATURE RANGE	-55°C~125°C
工作温度范围	OPERATING TEMPERATURE RANGE	0°C~70°C, -40~85°C
输入电压	INPUT VOLTAGE	5 & 3V±5%
最大输入电流	MAX.INPUT CURRENT	5~80mA
电平	LOGIC "1" / "0"	90%V _{DD} Min/10%V _{DD} Max
输出占空比	OUTPUT SYMMETRY	45/55% @ 1/2V _{DD}
输出上升/下降时间	OUTPUT RISE/FALL TIME	10nSec. Max.
负载	OUTPUT LOAD TTL/HCMOS	10TTL Gates/50pF HCMOS Max.
选择	OPTIONS ON PIN1	"1" = Enable, "0" = Sisable N/C=No Connection

外观尺寸 DIMENSION(UNIT:mm)

