



Data Sheet

Band4 Duplexer 1814

SPT1G73ADC1

2021/11/30
V1.2

Description:

The Spectron SPT1G73ADC1 is a miniature B4 duplexer designed for applications in LTE-A, 5G NR, customer premise equipment, and mobile communication devices.

The SPT1G73ADC1 provides +29 dBm power handling, low insertion loss and high out of band rejection.

The design and manufacturing of the SPT1G73ADC1 exploit Spectron's exclusive TSAW technology to deliver competitive performance against the state-of-the-art. at a low cost.

The SPT1G73ADC1 is compatible with high volume, lead-free SMT soldering processes.

Features:

- Single-Ended Input and Output
- Terminating Impedance: 50 Ω
- Compact miniature size
 - 1.8 mm \times 1.4 mm footprint
 - 0.65 mm max-height
- Environmental
 - RoHS 6 Compliant

Specifications:

- Performance specified from -20°C to +85°C
- In-band insertion loss: 2.4 dB Max for UL band
- In-band insertion loss: 2.5 dB Max for DL band
- High out of band rejection
- High isolation between Tx and Rx

Applications:

- LTE-A
- 5G NR
- Communication Devices

Electrical Specifications

Table 1 Electrical Specifications: Tx to Ant.

Tx to Ant			Specification		
Parameter	Condition [MHz]	Unit	Minimum ¹	Typical ²	Maximum ¹
Insertion Loss	1710.00 ~ 1755.00	dB	-	2.0	2.4
Inband Ripple	1710.00 ~ 1755.00	dB	-	0.4	1.2
VSWR of Tx Port	1710.00 ~ 1755.00	-	-	1.5	2
VSWR of Ant Port	1710.00 ~ 1755.00	-	-	1.6	2
Absolute Attenuation	10.00 ~ 728.00	dB	40	50	-
	699.00 ~ 716.00	dB	40	50	-
	704.00 ~ 716.00	dB	40	50	-
	716.00 ~ 746.00	dB	40	50	-
	777.00 ~ 787.00	dB	40	50	-
	824.00 ~ 849.00	dB	37	47	-
	851.00 ~ 894.00	dB	37	46	-
	1226.00 ~ 1250.00	dB	35	41	-
	1559.00 ~ 1563.00	dB	35	43	-
	1565.42 ~ 1573.37	dB	35	42	-
	1573.37 ~ 1577.46	dB	35	41	-
	1577.46 ~ 1585.42	dB	35	40	-
	1597.55 ~ 1605.89	dB	30	37	-
	1805.00 ~ 1880.00	dB	40	47	-
	1930.00 ~ 1990.00	dB	35	43	-
	2110.00 ~ 2155.00	dB	30	39	-
	2350.00 ~ 2360.00	dB	25	33	-
	2400.00 ~ 2494.00	dB	25	34	-
	2500.00 ~ 2570.00	dB	25	32	-
	3410.00 ~ 3520.00	dB	20	30	-
	4905.00 ~ 5267.00	dB	15	25	-
	4900.00 ~ 5950.00	dB	15	24	-
					-
					-
					-
					-
					-
					-

Table 2 Electrical Specifications: Ant to Rx.

Ant to Rx			Specification		
Parameter	Condition [MHz]	Unit	Minimum ¹	Typical ²	Maximum ¹
Insertion Loss	2110.00 ~ 2155.00	dB	-	2.0	2.5
Ripple Deviation	2110.00 ~ 2155.00	dB	-	0.5	1.2
VSWR of Rx Port	2110.00 ~ 2155.00	-	-	1.5	2.0
VSWR of Ant Port	2110.00 ~ 2155.00	-	-	1.4	2.0
Absolute Attenuation	10.00 ~ 699.00	dB	43	54	-
	400.00 ~ 400.00	dB	50	60	-
	699.00 ~ 714.00	dB	42	53	-
	777.00 ~ 787.00	dB	42	52	-
	824.00 ~ 849.00	dB	42	51	-
	1310.00 ~ 1355.00	dB	40	48	-
	1710.00 ~ 1755.00	dB	40	48	-
	1755.00 ~ 2025.00	dB	25	35	-
	1910.00 ~ 1955.00	dB	45	56	-
	2305.00 ~ 2315.00	dB	38	46	-
	2400.00 ~ 2500.00	dB	38	47	-
	2500.00 ~ 3820.00	dB	22	30	-
	3820.00 ~ 3910.00	dB	20	28	-
	4220.00 ~ 4310.00	dB	12	20	-
	4900.00 ~ 5950.00	dB	6	10	-

Table 3 Electrical Specifications: Tx to Rx.

Tx to Rx			Specification		
Parameters	Conditions [MHz]	Unit	Minimum ¹	Typical ²	Maximum ¹
Isolation	1710.00 ~ 1755.00	dB	50	52	-
	2110.00 ~ 2155.00	dB	45	47	-
	1574.00 ~ 1577.00	dB	55	57	-
	3410.00 ~ 3520.00	dB	55	59	-
	5120.00 ~ 5275.00	dB	20	24	-

1. Min/Max specifications are guaranteed over the indicated temperature range (unless otherwise noted).

2. Typical values are based on average measurements at +25 °C



Figure 1 Electrical Characteristics: Tx to Ant.**Figure 2** Electrical Characteristics: Tx to Ant.

Figure 3 Electrical Characteristics: Ant to Rx.




Figure 4 Electrical Characteristics: Ant to Rx.




Figure 5 Electrical Characteristics: Tx to Rx.




Figure 6 Electrical Characteristics: Tx to Rx.






Figure 7 Input Impedances.


Tx Input Impedance
(1710MHz to 1755MHz)




Rx Input Impedance
(2110MHz to 2155MHz)




Ant Input Impedance (Tx Band)



Ant Input Impedance (Rx Band)



Package & Dimensions¹




Marking Description	
XX	Band Code
#	Month Code
*	Date Code

Pin Configuration	
3	Tx
1	Rx
6	Antenna
2,4,5,7,8	Ground

1. All dimensions are in millimeters. Angles are in degrees.

Matching



Port	Matching Component ¹
Tx	L1 : 3.1 nH (Ideal inductor)
Rx	L2 : 1.1 nH (Ideal inductor)
Ant	L3 : 3.5 nH (Ideal inductor)


1. Matching component values shown are recommended based on Spectron evaluation board. Value adjustment may be required on the end-user's circuit boards for the selected component manufacturer and PCB material.

Maximum Ratings¹

Characteristic	Rating	Unit
Operating Temperature ²	-20 ~ +85	°C
Storage Temperature	-40 ~ +85	°C
Maximum Input Power ^{3,4}	+29	dBm
DC Voltage Between The Terminals ⁵	3	V
ESD Voltage (HBM)	> 100	V
ESD Voltage (CDM)	> 100	V
Moisture Sensitivity Levels	3	/

1. Operation exceeding any one of these conditions may result in permanent damage to the device.
2. The device will function over the recommended range without degradation in reliability or permanent change in performance but is not guaranteed to meet electrical specifications.
3. LTE modulation. Applies over a temperature range of TC = -20° to +85°C.
4. Maximum input power is only specified for input power to Tx port of SPT1G73ADC1 (Pin 3).
5. The DC resistance from Pin 1 and 3 (Tx/Rx) and Pin 6 (Ant) to ground (2-7) of this device is typically hundreds of kΩ to MΩ.

Recommended SMT Solder Profile



Ordering Information

Part Number	Number of Devices	Container
SPT1G73ADC1	4000pcs	Tape and Reel

Important Notice

Spectron Technologies, Spectron Microsystems, and the Spectron logo are among the trademarks of Spectron and/or its affiliates in the People's Republic of China, certain other countries, and/or the EU.

Copyright © 2022 Spectron. All Rights Reserved.

The term "Spectron" refers to Specton (Shenzhen) Technologies Co. Ltd and its subsidiaries.

Information furnished by Spectron is believed to be accurate and reliable. Spectron reserves the right to make changes without further notice to any products or data herein to improve reliability, function, or design. However, Spectron does not assume any liability arising from the application or use of this information nor the application or use of any product or circuit described herein. Neither does Spectron convey any license under its patent rights nor the rights of others.